



**LI·EN·TEC**  
WIRED TO GROW

**Leistung + Treiber für Rot LH351H LED-Strip**  
Datasheet  
Vers.2

### Lientec 28cm Rot LH351H LED Strip:

Mean Well Treiber (Konstantstromquelle)	Effizienz bei 230 VAC (max.)	DC Ausgangsspg.	mögliche Anzahl von 28cm Strips	LED-Leistung in Watt je nach Strip Anzahl
APC-8-350	81,50%	11-25V	1	4
APC-12-350	82,00%	9-36V	2	8
APC-16-350	84,00%	12-48V	3	12
LPC-20-350	83,00%	9-48V	2-4	8-16
HLG-60H-C350B	91,00%	100-200V	9-14	36-56
HLG-80H-C350B	91,50%	167-257V	14-20	56-80
HLG-120H-C350B	94,00%	215-430V	18-34	72-136
ELG-75-C350B	91,00%	107-214V	10-18	40-72
ELG-100-C350B	91,00%	143-286V	12-24	48-96
APC-8-500	81,00%	8-16V	1	6
APC-25-500	83,00%	15-50V	2-3	12/18
HLG-120H-C500B	94,00%	150-300V	12-23	72-138
HLG-185H-C500B	94,00%	200-400V	16-30	96-180
ELG-75-C500B	91,00%	75-150V	6-12	36-72
ELG-100-C500B	91,00%	100-200V	8-16	48-96
ELG-150-C500B	92,00%	150-300V	12-24	72-144
APC-12-700	80,00%	9-18V	1	9
LPC-20-700	83,00%	9-30V	1-2	9/18
LPC-35-700	85,00%	9-48V	1-3	9-27
HLG-60H-C700B	91,00%	50-100V	4-7	36-63
HLG-80H-C700B	91,50%	84-129V	6-9	54-80
HLG-120H-C700B	94,00%	107-215V	8-15	72-135
HLG-185H-C700B	94,00%	143-286V	11-20	99-180
HLG-240H-C700B	93,50%	178-357V	14-25	126-225
HLG-320H-C700B	94,00%	214-428V	16-34	144-306
ELG-75-C700B	90,00%	53-107V	4-8	36-72
ELG-100-C700B	90,00%	71-143V	6-11	54-99
ELG-150-C700B	92,00%	107-214V	8-16	72-144
ELG-200-C700B	93,00%	142-286V	11-22	99-198

**Li·En·Tec GmbH**  
Himmelmoorweg 24

25451 Quickborn

Tel.: +49 4106 6404780

[www.lientec-led.com](http://www.lientec-led.com) All rights reserved.

Fax: +49 4106 653171

**Lientec 56cm Rot LH351H LED Strip:**

Mean Well Treiber (Konstantstromquelle)	Effizienz bei 230 VAC (max.)	DC Ausgangsspg.	mögliche Anzahl von 28cm Strips	LED-Leistung in Watt je nach Strip Anzahl
APC-12-350	82,00%	9-36V	1	8
LPC-20-350	83,00%	9-48V	1-2	8/16
HLG-60H-C350B	91,00%	100-200V	4-7	32-56
HLG-80H-C350B	91,50%	167-257V	7-10	56-80
HLG-120H-C350B	94,00%	215-430V	9-17	72-136
ELG-75-C350B	91,00%	107-214V	5-9	40-72
ELG-100-C350B	91,00%	143-286V	6-12	48-96
HLG-120H-C500B	94,00%	150-300V	7-12	84-144
HLG-185H-C500B	94,00%	200-400V	9-15	108-180
ELG-75-C500B	91,00%	75-150V	4-6	48-72
ELG-100-C500B	91,00%	100-200V	5-8	60-96
ELG-150-C500B	92,00%	150-300V	7-12	84-144
LPC-20-700	83,00%	9-30V	1	19
LPC-35-700	85,00%	9-48V	1	19
HLG-60H-C700B	91,00%	50-100V	3	57
HLG-80H-C700B	91,50%	84-129V	4	76
HLG-120H-C700B	94,00%	107-215V	5-7	95-133
HLG-185H-C700B	94,00%	143-286V	6-10	114-190
HLG-240H-C700B	93,50%	178-357V	8-13	152-247
HLG-320H-C700B	94,00%	214-428V	9-16	171-304
ELG-75-C700B	90,00%	53-107V	3-4	57-75
ELG-100-C700B	90,00%	71-143V	3-5	57-95
ELG-150-C700B	92,00%	107-214V	5-7	95-133
ELG-200-C700B	93,00%	142-286V	6-10	114-190

**Lientec 112cm Rot LH351H LED Strip:**

Mean Well Treiber (Konstantstromquelle)	Effizienz bei 230 VAC (max.)	DC Ausgangsspg.	mögliche Anzahl von 28cm Strips	LED-Leistung in Watt je nach Strip Anzahl
LPC-20-350	83,00%	9-48V	1	16
HLG-60H-C350B	91,00%	100-200V	2-4	32-64
HLG-80H-C350B	91,50%	167-257V	3-5	48-80
HLG-120H-C350B	94,00%	215-430V	4-8	64-128
ELG-75-C350B	91,00%	107-214V	2-4	32-64
ELG-100-C350B	91,00%	143-286V	3-6	48-96
HLG-120H-C500B	94,00%	150-300V	3-6	72-144
HLG-185H-C500B	94,00%	200-400V	4-8	96-192
ELG-75-C500B	91,00%	75-150V	2-3	48-72
ELG-100-C500B	91,00%	100-200V	2-4	48-96
ELG-150-C500B	92,00%	150-300V	3-6	72-144
HLG-60H-C700B	91,00%	50-100V	1	38
HLG-80H-C700B	91,50%	84-129V	2	76
HLG-120H-C700B	94,00%	107-215V	3	114-150
HLG-185H-C700B	94,00%	143-286V	4-5	114-190
HLG-240H-C700B	93,50%	178-357V	4-6	152-228
HLG-320H-C700B	94,00%	214-428V	5-8	190-304
ELG-75-C700B	90,00%	53-107V	1-2	38-75
ELG-100-C700B	90,00%	71-143V	2	76
ELG-150-C700B	92,00%	107-214V	3-4	114-150
ELG-200-C700B	93,00%	142-286V	3-5	114-190